

DT-5K

Keyboard with Integrated HulaPoint II™

The DT-5K combines HulaPoint II™, an upgraded pointing device that offers improved sensitivity and increased durability, with a 10-key numeric keypad in a ruggedized stainless steel case, providing dual functionality in one compact unit. Its 20 function keys provide user versatility. This keyboard also offers user Windows keys for ease of access to the operating system.



Technical Specifications

Certifications

NEMA 4X
UL60950, FCC Part 15 Class B

Key Switch

MATERIAL: Industrial silicone rubber
LIFE: 10 million cycles
TRAVEL: 0.055 in.
ACTUATION FORCE: 200g (+/- 20g)
FEEDBACK: Tactile with mechanical snap

Power

PS/2 or AT/Serial: KEYBOARD: 50mA@5V (from Keyboard port)
HULAPOINT: 35mA@5V (from Mouse port)
USB: 85mA@5V (from CPU port)

Temperature Range

STORAGE: -40C to +70C
OPERATING: -20C to +60C

Humidity

100%

Shock

3x11 ms pulses of 50g on each of 3 axes

Vibration

POWER SPECTRAL DENSITY: 0.04g/Hz
FREQUENCY RANGE: 20Hz - 2 kHz
DURATION OF TEST PER AXIS: 3 hours

Flammability

PRINTED CIRCUIT BOARD: 94 VO
SILICONE OVERLAY: 94 HB
INTERFACE CABLE: 94 VO

Weight

5.25 lbs (2.38 kg)

Dimensions

16.25" x 7.88" x 1.80" (w-h-d)
412.8mm x 200.2mm x 45.7mm

Cable

LENGTH: 10 feet (3 meters)
DESIGN: "Y" PS/2 Cable (providing separate keyboard and mouse connections), or Single-Cable USB

Compatibility

PS/2 KEYBOARD/HULAPOINT: All Windows Operating Systems
USB KEYBOARD/HULAPOINT: All Windows and Macintosh OS

Warranty

1 year limited warranty

Model Numbers

DT-5K-PS2: With PS/2 cable
DT-5K-USB: With USB cable
DT-5K-STD: With AT/serial cable

Features and Benefits

- Integrated HulaPoint II™ Pointing Device
- 20 Function Keys
- 16.25" x 7.88" x 1.80" (w-h-d)
- USB, PS/2 and AT/serial configurations available
- 10-Key Numeric Pad
- 113-Key Functionality