

PX207W-J

7" TFT 1024x600 with
Intel Celeron CPU
Windows 10.0



Ordering Information

PX207WC-J6	7" Capacitive, Intel Celeron J6412
PX207WR-J6	7" Resistive, Intel Celeron J6412

Hardware

Intel Celeron J6412 (2.0GHz)
J6412: 8GB RAM, 256GB Flash
J6412: 2 x GbE RJ-45
1 x RS232 (422/485 option)
WiFi 2.4G & 5G, BT 4.0, (SIM/GPS option)
2 x USB 2.0, 2 x USB 3.0
1 x HDMI, 1 x VGA
1 x Line-out/Mic-in, 2 x built-in Speakers

Mechanical

Dimension 225 (W) x 160.7 (H) x 59.0 (D) mm
Net weight 1.9 (Kgs)
Cut-out 210.9 (W) x 146.5 (H)
Panel Mount, VESA 75x75/100x100
Aluminum front bezel and chassis

Display & Touch

7" TFT-LCD, 1024x600
Brightness 250 (cd/m ²)
View angle 160/160 (H°/V°)
Backlight Lifetime 50,000 hours
Contrast 1000:1
Capacitive/Resistive touch

OS & Power

Win 10 / Linux
12~24VDC, < 48 watts
**Screw Locking Terminal Block Adaptor

Environmental

IP65 Front
Op. Temp -10°C ~ 50°C
Storage Temp. -20°C ~ 70°C
10% to 90% @ 40°C (non-condensing)
CE/FCC (EN 55022, EN 55024, EN 61000-3-2, EN 61000-3-3)

